

**NBWA SAFETY TRAINING VIDEO
FORKLIFT SAFETY**

Name: _____

Date: _____

Please either circle correct answer or complete the sentence.

1. If you are transporting an oversized pallet, you should make sure you use fork extensions to maintain support and a safe load center.
2. Never transport pallets stacked above _____ pallet height
 - a. 1 pallet
 - b. 2 pallets
 - c. 3 pallets
3. A forklift should not be turned while forks are elevated _____ feet above the ground. This can move the combined center of gravity outside the stability triangle and cause a tip over.
 - a. 1 foot
 - b. 2 feet
 - c. 3 feet
4. Do not stack materials in
 - a. Main aisles
 - b. Front of doors
 - c. Blocking fire extinguishers, fire hoses, & safety equipment
 - d. All of the above
5. Slow down and Sound your horn when approaching intersections, crossing aisles, and locations where your vision is obstructed.
6. Follow other vehicles at a safe distance, usually a minimum of 3 truck lengths, or 3 seconds passing the same spot .
7. Always slow down to turn and keep the forks as low as possible to clear uneven surfaces or debris of 4-6 inches at the tips, or 1-2 inches at the heels .
8. Vehicles shall not be driven in and out of trailers until
 - a. Trailers are securely blocked
 - b. Brakes are set
 - c. The floor is determined to be safe
 - d. All of the above
9. If at any time during operation, the lift truck is found to be in need of repair, defective, or in any way unsafe, you should report it to your supervisor. The truck must be tagged out of service until it has been restored to safe operating condition.

Employee Signature